

Hose Clamps


Our hose clamps are manufactured to DIN 3015 with a practical and economical design. Using weldable plates its easy to anchor the clamps to machinery and steelworks. The collars are manufactured in Polypropylene with ribbed clamp half for standard and double series or Aluminium for heavy duty series.

Note: When a bend is supported by clamps, the clamps should be positioned as close as possible to each side of the bend.

Recommended distance for installation of clamps of the same group code

Hose OD mm	Distance of clamps Metres
6 - 12.7	0.9
15 - 22	1.2
23 - 28	1.5
30 - 38.1	2.0
40 - 48.3	2.5
50 - 57	3.0

Hose OD mm	Distance of clamps Metres
60 - 70	3.4
76.1 - 88.9	3.7
101.6 - 108	4.0
114.3 - 133	4.3
139.7 - 165.1	5.0
169.3 - 324	5.5



Available in Aluminium on request

Single Hose Clamp (Polypropylene)

•Complete hose clamp supplied assembled

GROUP	A	B	C	D	F	S	Bolt	HOSE OD	PART NUMBER
1	30	34	20	27	42	3	M6X30	6	RS106
								10	RS110
								12	RS112
2	30	40	26	33	48	3	M6X35	14	RS214
								15	RS215
								16	RS216
								18	RS218
3	30	48	33	35	55	3	M6X40	20	RS320
								22	RS322
								25	RS325
4	30	57	40	42	62	3	M6X45	28	RS428
								30	RS430
5	30	68	52	58	74	3	M6X60	35	RS535
								38	RS538
6	30	86	66	66	88	3	M6X70	48.3	RS6112
								50.8	RS6508

Single Hose Clamp Components (Polypropylene)

GROUP	BOTTOM PLATE	TOP PLATE	BOLT (2 REQUIRED)	HOSE OD	CLAMP BODY
2	APIN2	APS2	M635DIN931	16	A216S
3	APIN3	APS3	M640DIN931	22	A322S
4	APIN4	-	M645DIN931	-	-
5	-	-	M660DIN931	35	A535S